



Nexans Ref.: 10513967
EAN 13: 5413404297023

FIRE PERFORMANCE CLASS



Cca-s1,d1,a1

CONTACT

Product Management
service.nnl@nexans.com

Nexans YMz1K Cca is a halogen free power cable according to fire classification Cca-s1,d1,a1 for connection in low voltage installation up to 0.6/1 kV in construction works with a high fire hazard level. ALSECURE® YMz1K Cca FLEX provided with conductors with increased bendability (FLEX)

STANDARDS

Product HD 604 S1 part 5/sect. C; IEC 60228

APPLICATION

Nexans YMz1K Cca is a halogen free low smoke power cable for general use in construction works subject to performance requirements on reaction to fire. **Nexans YMz1K Cca** is suitable for application in low voltage installations up to 0.6/1 kV, according to NEN 1010. It meets the requirements according to fire classification Cca-s1,d1,a1 for buildings and civil engineering works with a high fire hazard level (NEN 8012).

Available from 35 mm²: Nexans YMz1K Cca FLEX, provided with conductors with increased bendability.

MAIN BENEFITS

Easy Strippable- Cables (1.5 - 6 mm²) are easy to strip

PEP EcoPassport - EPD environmental passport available

UV Resistant - Our cables passed the 720 hour test according to the test standard EN 50289-4-17 Method A

Design

1. Conductor
Sections till 10 mm²: Bare copper, solid , class 1
Sections from 10 mm²: Bare copper, stranded, class 2
2. Insulation: XLPE
3. Inner covering: Halogen free compound
4. Outer sheath: Halogen free compound
Colour: grey
UV resistance: Yes



Conductor flexibility
Stranded class 2



Halogen free
Yes



Rated Voltage U₀/U
(Um)
0,6/1 kV



Mechanical
resistance to
impacts
Good



Bending factor
when laying
10 (xD)



Minimum
installation
temperature
0 °C



Operating temp.
-20 ... 80 °C



Max. conductor
temp.in service
90 °C

CHARACTERISTICS

Construction characteristics

Conductor flexibility	Stranded class 2
Insulation	XLPE (Cross-linked Polyethylene)
Core identification	Natural
Conductor material	Copper class 2
Outer sheath	Halogen free compound
Sheath colour	Grey
Halogen free	Yes
Conductor shape	Round, multi stranded
With Green/Yellow core	No

Dimensional characteristics

Number of cores	1
Conductor cross-section	35 mm ²
Nominal outer diameter	12.5 mm
Approximate weight	405 kg/km
Average insulation thickness	0.9 mm
Nominal outer sheath thickness	1.4 mm

Electrical characteristics

Permissible current rating in open air	201 A
Rated Voltage U ₀ /U (U _m)	0,6/1 kV

Mechanical characteristics

Mechanical resistance to impacts	Good
----------------------------------	------

Usage characteristics

Bending factor when laying	10 (xD)
One single bending at each end minimum	8 (xD)
Field of application	Standard
Minimum installation temperature	0 °C
Operating temperature, range	-20 ... 80 °C
Max. conductor temperature in service	90 °C
U.V resistance	EN 50289-4-17 method A, for 720h

SELLING AND DELIVERY INFORMATION

Marking

ALSECURE YMz1K Cca n (x or G) s mm²
 NEXANS BENELUX
 KEMA KEUR
 Meter Marking

Core identification

- 1 core: neutral
- 2 cores: brown - light blue
- 3G cores: green/yellow - light blue - brown

- 3x cores: black -grey- brown
- 4 cores: green/yellow - brown-black-grey
- 5 cores: green/yellow - light blue - brown - black - grey