



Nexans Ref.: 10533331  
 EAN 13: 5413404304400

**FIRE PERFORMANCE CLASS**



Eca



**CONTACT**

Product Management  
 service.nnl@nexans.com

H07V-U Eca is an installation wire in a handy VOBbox / VDbox. H07V-U Eca is a solid PVC installation wire intended for protected fixed domestic and industrial installations. Installation may be in pipes or gutters embedded in the wall or floor or surface mounted. H07V-U Eca has a very low friction factor which makes it easy to slide and pull into pipes. In addition, H07V-U Eca is **easy to strip**, making it quick to process. **The box of the VOBbox has the same color as the wire in it.** The section is also clearly legible on all sides. This ensures that you have the right wire in place immediately. The cardboard of the VOBbox-VDbox is also **extra moisture-resistant**, ideal for damp construction sites. Furthermore, the box is designed to keep spiral formation to a minimum. This further **facilitates the wire pulling and makes it even easier to work with.** H07V-U Eca meets fire class Eca according to EN 50575.

**STANDARDS**

Product EN 50525-2-31; IEC 60228

**APPLICATION**

The colored box packaging **VOBbox (VDbox in The Netherlands)** is made of special strong moisture resistant cardboard. Easy to use in humid conditions or in bad weather. The **VOBbox** is available in different colors, with the color of the box corresponding to the color of the wire inside.

**H07V-U Eca** is an installation wire according to fire classification Eca for use indoor in residential and similar installations with a low fire hazard level. They have a low friction coefficient and are suitable for fixed installation in tubes or skirting-board systems.

**DESIGN**

- Conductor: Bare copper, solid, class 1
- Insulation: Special PVC, with enhanced sliding properties
- Section: 1.5 mm<sup>2</sup> and 2.5 mm<sup>2</sup>
- Packaging: 100m in the VOBbox (VDbox), a moisture-proof cardboard with color recognition
- Available colours: Green/yellow, brown, blue, black, grey, red, orange and black-white



Conductor flexibility  
 Solid class 1



Halogen free  
 No



Rated Voltage Uo/U  
 (Um)  
 450/750 V



Bending factor  
 when laying  
 4 (xD)



Max. conductor  
 temp. in service  
 70 °C



Operating temp.  
 -15 ... 70 °C



Chemical  
 resistance  
 Medium



Minimum  
 installation  
 temperature  
 5 °C

## CHARACTERISTICS

### Construction characteristics

Conductor material	Copper
Conductor shape	Round, massive
Conductor flexibility	Solid class 1
Insulation	PVC
Wire colour	Blue
Halogen free	No

### Dimensional characteristics

Number of cores	1
Conductor cross-section	2.5 mm <sup>2</sup>
Average insulation thickness	0.8 mm
Nominal outer diameter	3.4 mm
Approximate weight	30 kg/km

### Electrical characteristics

Rated Voltage U <sub>0</sub> /U (U <sub>m</sub> )	450/750 V
Permissible current rating in open air	24 A
Voltage drop, single phase	14.8 V/A.km

### Usage characteristics

Bending factor when laying	4 (xD)
Field of application	Indoor
Max. conductor temperature in service	70 °C
Operating temperature, range	-15 ... 70 °C
Resistance to vibrations	Moderate
Chemical resistance	Medium
Packaging	Box
Length	100 m
Minimum installation temperature	5 °C