



D_{ca}

Nexans Ref.: 10559869
EAN 13: 5413404321513

FIRE PERFORMANCE CLASS



Dca-s2,d2,a3



CONTACT

Product Management
service.nnl@nexans.com

Power cable according to Dutch standard with fire classification Dca-s2,d2,a3 for usage in low voltage installations up to 0.6/1 kV in housing, residential and similar installation with a medium fire hazard level

STANDARDS

Product HD 604.4D; IEC 60228

Test KEMA 42 C-1-4-D

APPLICATIONS

YMvK Dca 0.6/1 kV is a power cable for general use in construction works subject to performance requirements on reaction to fire. **YMvK Dca 0.6/1 kV** is suitable for application in low voltage installations up to 0.6/1 kV, according to NEN 1010. It meets the requirements according to fire classification **Dca-s2,d2,a3** for usage in buildings and civil engineering works with a medium fire hazard level (NEN 8012).

Thanks to its improved flexibility **YMvK Dca-s2 FLEX 0.6/1 kV** is easier to install than the non-flexible version. **YMvK Dca FLEX 0.6.1 kV** is available from 35 mm².

YMvK Dca-s2 0.6/1 kV Easy Strippable has an improved design with an easier to strip cable sheaths. With **Easy Strippable** you can remove the sheath in a single smooth motion over a length of up to 100 cm.

Design

1. Conductor:
Conductors until 10 mm²: Bare copper, solid, class 1
Conductors from 10 mm²: Bare copper, stranded, class 2
2. Insulation: XLPE
3. Inner covering: filling compound
4. Outer sheath: PVC
Colour: Grey
UV resistance: Yes

CORE IDENTIFICATION

- 1 core : black
- 2 cores : brown - blue
- 3G cores: brown - blue - green/yellow
- 3x cores : black - brown - grey
- 4 cores : brown - black - grey - green/yellow
- 5 cores : brown - blue - black - grey - green/yellow



Conductor flexibility
Solid class 1



Lead free
Yes



Rated Voltage Uo/U
(Um)
0,6/1 kV



Mechanical
resistance to
impacts
Good



Bending factor
when laying
10 (xD)



Minimum
installation
temperature
0 °C



Operating temp.
-20 ... 80 °C



Max. conductor
temp. in service
90 °C

CHARACTERISTICS

Construction characteristics

With Green/Yellow core	Yes
Core identification	Brown, black, grey, green / yellow
Sheath colour	Grey
Conductor shape	Round solid
Conductor material	Bare copper
Insulation	XLPE (chemical)
Protection	Filler
Outer sheath	PVC
Conductor flexibility	Solid class 1
Lead free	Yes

Dimensional characteristics

Number of cores	4
Conductor cross-section	1.5 mm ²
Approximate weight	196 kg/km
Nominal outer diameter	11.6 mm
Average insulation thickness	0.7 mm
Nominal outer sheath thickness	1.8 mm

Electrical characteristics

Loop resistance, max. at 20°C	12.1 Ohm/km
Permissible current rating in open air	23 A
Rated Voltage U ₀ /U (U _m)	0,6/1 kV









Mechanical characteristics

Mechanical resistance to impacts	Good
----------------------------------	------













Usage characteristics

Field of application	Standard
Bending factor when laying	10 (xD)
One single bending at each end minimum	8 (xD)
Minimum installation temperature	0 °C
Operating temperature, range	-20 ... 80 °C
Max. conductor temperature in service	90 °C
Packaging	Cut to length
U.V resistance	EN 50289-4-17 method A, for 720h















CURRENT CAPACITY TABLE PR SINGLE PHASE SINGLE CORE

Conductor cross-section [mm²]	 Cu	 Cu	 Cu	 Cu
1.5	19	23	24	-
 A1 Insulated conductors in conduit in a thermally insulated wall	 B1 Insulated conductors in conduit on a wooden wall	 C Single-core or multi-core cable on a wooden wall		
 F Single-core flat cables, touching in free air				













CURRENT CAPACITY TABLE PR SINGLE PHASE MULTICORE

Conductor cross-section [mm²]	 Cu	 Cu	 Cu	 Cu	 Cu	 Cu
1.5	19	22	25	24	27	26
 A2 Multi-core cable in conduit in a thermally insulated wall	 B2 Multi-core cable in conduit on a wooden wall			 C Single-core or multi-core cable on a wooden wall		
 D1 Multi-core cable in ducts in the ground	 D2 Multi-core cables designed to be buried directly in the ground			 E Multi-core cable in free air		

CURRENT CAPACITY TABLE PR THREE PHASE SINGLE CORE

Conductor cross-section								
[mm²]		Cu	Cu	Cu	Cu	Cu	Cu	Cu
1.5		17	20	21	22	23	-	-
	A1 Insulated conductors in conduit in a thermally insulated wall		B1 Insulated conductors in conduit on a wooden wall				D1 Single or Multi-core cable in ducts in the ground	
	C Single-core or multi-core cable on a wooden wall		D2 Single or Multi-core cables designed to be buried directly in the ground				F Single-core trefoil cables, touching in free air	
	F Single-core flat cables, touching in free air							

CURRENT CAPACITY TABLE PR THREE PHASE MULTICORE NL

Conductor cross-section [mm²]	 Cu	 Cu	 Cu	 Cu	 Cu	 Cu
1.5	17	20	21	22	23	23
 A2 Multi-core cable in conduit in a thermally insulated wall	 B2 Multi-core cable in conduit on a wooden wall			 D1 Multi-core cable in ducts in the ground		
 C Single-core or multi-core cable on a wooden wall	 D2 Multi-core cables designed to be buried directly in the ground			 E Multi-core cable in free air		

SELLING AND DELIVERY INFORMATION**Marking**

YMvK Dca (FLEX) n (x or G) s mm²
NEXANS BENELUX
KEMA KEUR
Meter Marking